

SERVICE CONNECTION FITTINGS SCHEDULE - 100mm DIA. CONNECTION			
FITTING	DIA (mm)	DESCRIPTION	QTY.
1	160 O.D.x110 I.D.	uPVC TYPE "A" 45 WYE JUNCTION	1
2	160 O.D.	uPVC SLIP COUPLING, SN16, M-RING RUBBER RING JOINTS, NO CENTRE REGISTER	2
3	110 O.D.	uPVC PLAIN ENDED PIPE, SN16 PLAIN WALL, LENGTH TO SUIT	1
4	110 I.D.	uPVC SCREW CAP FITTING, SN16 (INCLUDING CAP)	1
SERVICE CONNECTION FITTINGS SCHEDULE - 150mm DIA. CONNECTION			
FITTING	DIA (mm)	DESCRIPTION	QTY.
1	160 O.D.x160 I.D.	uPVC TYPE "A" 45 WYE JUNCTION BY SOLO PLASTICS LTD.	1
2	160 O.D.	uPVC SLIP COUPLING, SN16, M-RING RUBBER RING JOINTS, NO CENTRE REGISTER	2
3	160 O.D.	uPVC PLAIN ENDED PIPE, SN16, LENGTH TO SUIT	1
4	160 I.D.	uPVC SCREW CAP FITTING, SN16 (INCLUDING CAP)	1

NOTES:

1) Solvent cement and cleaner primer shall be of approved make eg. Novakey or similar.



STANDARD DETAIL:

STORMWATER SERVICE CONNECTION DETAILS 160MM O.D. UPVC PUBLIC DRAIN DATE: June 2010 NOT TO SCALE

TCDC NO: SHEET NO: REV:

6000

6